

	Order no.	Packing unit	PS
--	--------------	-----------------	----



SCHUKO socket outlet 16 A/250 V~
with inscription space,
child protection and symbol

cream white glossy	0462 01	1/5	01
pure white glossy	0462 03	1/5	01
pure white matt	0462 27	1/5	01
anthracite	0462 28	1/5	11
colour aluminium	0462 26	1/5	11

with green labelling SV for safety supply¹⁾

cream white glossy	0438 01	1/5	01
pure white glossy	0438 03	1/5	01
pure white matt	0438 27	1/5	01
anthracite	0438 28	1/5	11
colour aluminium	0438 26	1/5	11

with orange labelling ZSV for additional safety supply¹⁾

cream white glossy	0427 01	1/5	01
pure white glossy	0427 03	1/5	01
pure white matt	0427 27	1/5	01
anthracite	0427 28	1/5	11
colour aluminium	0427 26	1/5	11

with red labelling WSV for additional safety supply¹⁾

cream white glossy	0421 01	1/5	01
pure white glossy	0421 03	1/5	01
pure white matt	0421 27	1/5	01
anthracite	0421 28	1/5	11
colour aluminium	0421 26	1/5	11

Increased contact protection pursuant to VDE 0620.

Inscription label „EDV“ is included.

¹⁾The bases of the SCHUKO socket outlets are marked with the respective colour.

Inscription sheets 1455 00 → Page 208.



SCHUKO socket outlet 16 A/250 V~
with hinged cover

cream white glossy	0454 01	1/5	01
pure white glossy	0454 03	1/5	01
pure white matt	0454 27	1/5	01
anthracite	0454 28	1/5	11
colour aluminium	0454 26	1/5	11

with child protection and symbol¹⁾

cream white glossy	0414 01	1/5	01
pure white glossy	0414 03	1/5	01
pure white matt	0414 27	1/5	01
anthracite	0414 28	1/5	11
colour aluminium	0414 26	1/5	11

with green cover plate for SV (safety supply)²⁾

green, glossy	0415 02	1/5	01
---------------	----------------	-----	----

**with orange cover plate for ZSV
(supplementary safety supply)²⁾**

orange, glossy	0416 02	1/5	01
----------------	----------------	-----	----

with red cover plate for WSV (additional safety supply)²⁾

red, glossy	0104 02	1/5	01
-------------	----------------	-----	----

Install in combination with the sealing set and cover frames
Standard 55 and E2, 1 to 5-gang, SCHUKO socket outlets with
hinged cover, water-protected, flush-mounted IP 44.

¹⁾Increased contact protection pursuant to VDE 0620.

²⁾The bases of the SCHUKO socket outlets are marked with the respective colour.

Sealing set 0252 27 → Page 42.

Cover frames Standard 55, 1 to 5-gang, 0211 .. to
0215 .. → Page 48.

Cover frames E2, 1 to 5-gang, 0211 .. to 0215 .. → Page 56.

	Order no.	Packing unit	PS
--	--------------	-----------------	----



SCHUKO socket outlet 16 A/250 V~
with control light
and inscription space

cream white glossy	0452 01	1/5	01
pure white glossy	0452 03	1/5	01
pure white matt	0452 27	1/5	01
anthracite	0452 28	1/5	11
colour aluminium	0452 26	1/5	11

with green labelling SV for safety supply¹⁾

cream white glossy	0468 01	1/5	01
pure white glossy	0468 03	1/5	01
pure white matt	0468 27	1/5	01
anthracite	0468 28	1/5	11
colour aluminium	0468 26	1/5	11

with orange labelling ZSV for additional safety supply¹⁾

cream white glossy	0469 01	1/5	01
pure white glossy	0469 03	1/5	01
pure white matt	0469 27	1/5	01
anthracite	0469 28	1/5	11
colour aluminium	0469 26	1/5	11

Inscription label „EDV“ is included.

¹⁾The bases of the SCHUKO socket outlets are marked with the respective colour.

Inscription sheets 1455 00 → Page 208.



SCHUKO socket outlet 16 A/250 V~
with LED orientation light,
child protection and symbol

cream white glossy	1170 01	1/5	02
pure white glossy	1170 03	1/5	02
pure white matt	1170 27	1/5	02
anthracite	1170 28	1/5	02
colour aluminium	1170 26	1/5	02

SCHUKO socket outlet with inserted light strip. The white LEDs project a light corridor downwards. This produces indirect orientation lighting that also avoids bothersome glare in bedrooms. The integrated twilight sensor waits until twilight to automatically switch on the LED light and switches it off again when sufficient daylight is detected. The LED light is completely integrated in the cover plate, eliminating the need for separate connection.

Power consumption:	0.25 W/0.35 VA/1.5 mA
Standby:	0.175 W/0.25 VA/1.0 mA
Light intensity:	0.2 cd
Protection type:	IP 20
Operating temperature:	-15 °C to +40 °C

Increased contact protection pursuant to VDE 0620.