

Order no.	Packing unit	PS
-----------	--------------	----

Push button sensor 2, 1-gang with controller



Push button sensor 2,
1-gang with controller
with inscription space

System 55			
transparent white	1061 100	1/5	06
E22			
Stainless steel (lacquered)	1061 20	1/5	06
Aluminium (lacquered)	1061 203	1/5	06
transparent white	1061 100	1/5	06
Bus coupler	0570 00	1/5	06

Disassembly safeguard implemented via its being screwed down.
Neutral inscription labels included.

Product family: Push button

Product type: Push button, 1-gang

The push button sensor is attached to a flush-mounted bus coupler.
The following software variants are to be programmed with ETS 2:

- Free assignment of the functions switching/pressing, dimming, blinds, value transmitter/light scene auxiliary unit, analogue value transmitter and universal value transmitter EIS 6 to the 2 buttons or 1 rocker
- Status indication via 2 red LEDs possible
- Inscription space illumination ON, OFF, automatic switch-off or switchable via object
- Blocker for blocking individual buttons or rockers
- Alarm message after removal of the flush-mounted bus interface (1 bit/1 byte telegram)
- Switching/pressing function (ON, OFF, SW, no function)
- Dimming with stop telegram and telegram repetition possible
- Single-surface operation for rocker functions (switching/pressing, dimming) possible
- Blind press function (UP/DOWN) and operating concept (STEP - MOVE - STEP or MOVE - STEP) can be set
- Press functions of value transmitter EIS 6 (1 byte) or light scene execution with/without memory function
- Analogue value transmitter (EIS 5 or EIS 10), value adjustment possible by pressing and holding button
- Universal value transmitter EIS 6 for continuous run-through of a value range

Back-lit, large-area inscription space (39 x 54 mm). Can be lit in accordance with the workplace ordinance.

Temperature range: -5 °C to +45 °C

Protection type: IP 20

Connection: 2 x 5-pole plug connector

For integration in Stainless Steel Series 20, Series 21:

Intermediate plate 55 x 55 mm 0289 20 → Page 97.

Inscription sheets 1090 00 → Page 209.

Instabus bus coupler 0570 00 → Page 350.

Order no.	Packing unit	PS
-----------	--------------	----



Push button sensor 2,
1-gang with controller
with inscription space

F100

cream white glossy	2061 111	1/5	06
pure white glossy	2061 112	1/5	06
Bus coupler	0570 00	1/5	06

Disassembly safeguard implemented via its being screwed down.
Neutral inscription labels included.

Product family: Push button

Product type: Push button, 1-gang

The push button sensor is attached to a flush-mounted bus coupler.

The following software variants are to be programmed with ETS 2:

- Free assignment of the functions switching/pressing, dimming, blind, value transmitter/light scene auxiliary unit, analogue value transmitter and universal value transmitter EIS 6 to the 2 buttons or 1 rocker
- Status indication via 2 blue LEDs possible
- Blocker for blocking individual buttons or rockers
- Alarm message after removal of the flush-mounted bus interface (1 bit/1 byte telegram)
- Switching/pressing function (ON, OFF, SW, no function)
- Dimming with stop telegram and telegram repetition possible
- Single-surface operation for rocker functions (switching/pressing, dimming) possible
- Blind press function (UP/DOWN) and operating concept (STEP - MOVE - STEP or MOVE - STEP) can be set
- Press functions of value transmitter EIS 6 (1 byte) or light scene execution with/without memory function
- Analogue value transmitter (EIS 5 or EIS 10), value adjustment possible by pressing and holding button
- Universal value transmitter EIS 6 for continuous run-through of a value range

Large-area inscription space (69 x 67 mm). Can be lit in accordance with the workplace ordinance.

Temperature range: -5 °C to +45 °C

Protection type: IP 20

Connection: 2 x 5-pole plug connector

Inscription sheets 2871 .. → Page 209.

Instabus bus coupler 0570 00 → Page 350.