

	Order no.	Packing unit	PS
	Instabus KNX/EIB USB data interface		
Flush-mounted	1070 00	1/5	06

Product family: System components
Product type: Interface

USB data interface with integrated bus coupler. It enables the connection of a PC for the addressing, programming and diagnosis of Instabus EIB components. The data interface is supported by the **ETS3** or the **ETS Starter** and the PC operation system Microsoft® Windows® ME, 2000 and XP.

Connections: Instabus via connection and branch terminal **0595 00**
USB pin jack, type B

Transfer protocol: compatible with USB 1.1/2.0
Temperature range: -5 °C to +45 °C
Protection type: IP 20

Suitable for cover plate 0276 .., 0876 ..
Instabus connection and branch terminal 0595 00 → Page 377.
USB connection cable 0903 00 → Page 351.


	USB connection cable		
	0903 00	1	06

USB connection cable for connecting the USB data interface flush-mounted or DRA to the PC. Plug type A-B.


Connection line: 3 m

USB data interface UP 1070 00 → Page 351.
USB data interface DRA 1080 00 → Page 356.


	Order no.	Packing unit	PS
Sensor inserts			

	Instabus KNX/EIB push-button bus coupler, 1-gang with single-point operation and status LED		
Flush-mounted	0181 00	1/5	06


Functional description → Page 310.

	Instabus KNX/EIB push-button bus coupler, 1-gang with two-point operation and status LED		
Flush-mounted	0184 00	1/5	06

Functional description → Page 310.

	Instabus KNX/EIB push-button bus coupler, 2-gang with single-point operation		
Flush-mounted	0182 00	1/5	06

Functional description → Page 310.

	Instabus KNX/EIB push-button bus coupler, 2-gang with two-point operation		
Flush-mounted	0185 00	1/5	06

Functional description → Page 310.